



Rhino™ Rigs

Comparison Chart



ISO 9001:2008
FM62236

		12ft	16ft	20ft	20ft	28ft
GVWR:	7,000	●	●			
	10,000			●		
	14,000				●	●
AXLE:	Tandem axle	●	●	●	●	●
SUSPENSION:	Torsion spring	●	●	●	●	●
BRAKES:	Electric with emergency break away stop	●	●	●	●	●
HITCH:	2-5/16 in ball	●	●	●	●	
	Gooseneck					●
STAND:	Front jack stand	●	●	●	●	
	Double landing gear					●
POWER:	(3) 220-volt receptacles			●	●	●
	GFI 110-volt interior wall receptacle (2 gang)			x4	x4	x5
	110-volt pkg with 30 amp panel / 100 amp 3 phase service			●	●	●
DOORS:	42 in entrance door with camber			●	●	●
	Barn doors	optional	optional	rear	rear	side
	Ramp with spring return	●	●	side	side	rear
LIGHTING:	4 ft double-tube fluorescent light with diffuser			x3	x3	x3
	12-volt interior dome light	x1	x1	x2	x2	x2
INTERIOR MISC:	13,500 BTU roof-mount air conditioner with heat strip			●	●	●
	Bead board wall & ceiling styrofoam insulation			●	●	●
	3/16 in white vinyl liner for interior ceiling			●	●	●
	Partition wall for generator compartment			●	●	●
	Vent pipe plate for generator exhaust			●	●	●
	White aluminum walls reinforced with 3/8 in plywood walls			●	●	●
	3/8 in plywood walls	●	●			
	Double-ply extra member rear area for generator support			●	●	●
	12 in x 12 in hose hatch			●	●	●
	(2) Equipment intake vents			●	●	●
	Refrigerant vents for back door					●
	Safety package	●	●	●	●	●
	(1) Overhead cabinet: 21 in h x 18 in w x 72 in l			●	●	●
	(2) Wall cabinets: 24 in h x 8 in w x 48 in l		optional			
	Work bench: 60 in l x 24 in w			●	●	●
	Four drawer tool box			●	●	●
	20227T Fire extinguisher (additional)		optional	optional	optional	optional
20495T Workbench vise			optional	optional	optional	
22007T Pail holders	optional	optional				
22004T Double drum brace (maximum 2)			optional	optional	optional	
22102T Triple drum brace (maximum 2)					optional	
20399T Hose mount		optional				
20407T Machine mounting kit		optional				
20406T Industrial hose brace			optional	optional	optional	
EQUIPMENT:	G255081 RhinoPro™ HP-21 Classic equipment (2:1)			●	●	●
	(Proportioner, G253382 RhinoPro™ HP-21 Max equipment (2:1)			●	●	●
	Hose & Gun/ RHP11E-10HH E-10 with heated hose (1:1)		●	●	●	●
	Attachment) GAP9034 E-20 (1:1)			●	●	●
	GAP9058 E-30 (1:1)			●	●	●
	GAP9033 E-XP1 (1:1)			●	●	●
	GAP9036 E-XP2 (1:1)			●	●	●
	15082 Fluid line package (transfer pumps)			●	●	●
	15083 Industrial transfer pump assembly		●	●	●	●
	20507 7 kw generator (for E-10)		●	●	●	●
GENERATOR:	22091 22 kw generator (20 kw min for E-20)			●	●	●
	20522 40 kw generator (40 kw min for Classic, Max, E-20, E-30, E-XP1, E-XP2)			●	●	●
COMPRESSOR:	49813009 IR compressor 5.5 hp Honda		●			
	2475N5-P 5 hp compressor, 25 cfm @ 100 psi			●	●	●
AIR DRYER:	23231822 D42IN refrigerated dryer			●	●	●
	15081 Air line package			●	●	●
MISC:	20513T Edco floor grinder	●	●			
	20505T Blastrac turbo vacuum	●	●			

Rhino™ Rigs